

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
9 December 2004 (09.12.2004)


PCT

(10) International Publication Number
WO 2004/107174 A1

- (51) International Patent Classification⁷: G06F 11/00
- (21) International Application Number: PCT/US2004/017199
- (22) International Filing Date: 28 May 2004 (28.05.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 60/473,756 28 May 2003 (28.05.2003) US
- (71) Applicant (for all designated States except US): SYMBOL TECHNOLOGIES, INC. [US/US]; One Symbol Plaza, Holtsville, NY 11742 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): KLEIN, John [US/US]; 220 La Via Azul Court, Morgan Hill, CA 95037 (US).
- (74) Agents: SCHEINFELD, Robert, C. et al.; Baker Botts L.L.P., 30 Rockefeller Plaza, New York, NY 10112-4498 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: BACKUP CELL CONTROLLER



(57) Abstract: A wireless local area network for data communications between a computer and mobile units is provided with at least two cell controllers connected to the computer and one or more rf ports each connected to a primary interface of one cell controller and to a backup interface of another cell controller. A control program in the cell controller monitors data communications between the other cell controller and the rf port by a backup interface. The program is arranged to cause the second cell controller to assume primary communications functions for the rf port in the event primary communications functions between a first cell controller and the rf port are inoperative.

Best Available Copy

WO 2004/107174 A1



FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report

BACKUP CELL CONTROLLER

SPECIFICATION

CROSS-REFERENCE TO RELATED APPLICATION

This application claims the benefit of U.S. provisional patent
5 application Serial No. 60/473,756, filed on May 28, 2004.

BACKGROUND OF THE INVENTION

This invention relates to wireless data communications networks, and
in particular to such networks in accordance with co-assigned and co-pending U.S.
10 Patent Application Serial No. 09/528,697, filed March 17, 2000, which is hereby
incorporated by reference herein its entirety.

US Patent Application Serial No. 09/528,697 discloses an arrangement
for wireless local area networks, and particularly arrangement for wireless networks
using the radio data communications protocol of IEEE Standard 802.11, such as the
15 Spectrum 24 system which is available from the assignee of this application. In the
referenced prior application there is disclosed an arrangement wherein access points
used for a conventional IEEE Standard 802.11 wireless data communication system
are replaced by simplified devices called "rf ports" in the prior application. The rf
ports are connected by an interface to cell controllers which are computers
20 programmed to perform much of the higher level MAC functions required of an
access point according to Standard 802.11. As indicated in the referenced prior
application, the rf ports can be simplified devices which are supplied with power over
the data communications cable from the location of the cell controller. Accordingly
the rf ports provide a simplified device, not only for manufacture, but also for
25 installation.

One consideration with the arrangements as described in the referenced
prior application is that a failure of a cell controller can result in a failure of
communications between a wired network and the rf ports associated with that cell
controller. Since a cell controller is responsible for performing higher level Standard

802.11 MAC functions of the access points, a large number of rf ports may be serviced by a single cell controller, and failure of the cell controller can result in failure of the wireless data communications network over a relatively large area. In systems which use self sufficient access points to provide wireless access to a network, the failure of an access point does not necessarily result in system failure, since access points in adjoining physical location can continue to provide communications for a mobile unit which was communicating through the failed access point.

It is an object of the present invention to provide an improved method and apparatus for use in a system using a cell controller and rf port for providing wireless local area network communications.

SUMMARY OF THE INVENTION

In accordance with the invention there is provided a wireless local area network for data communications between a computer and at least one mobile unit. The network includes first and second cell controllers connected to the computer, for example, through a wired data communications network. There is provided at least one rf port connected to a primary interface of the first cell controller and to a backup interface of the second cell controller. The second cell controller includes a control program for monitoring data communications with the rf port via the backup interface. The program is arranged to cause the second cell controller to assume primary communications functions of the rf port in the event primary communications functions of the first cell controller are inoperative for communication with the rf port.

According to a preferred arrangement of the wireless local area network there may be provided at least one additional rf port which is connected to a primary interface of the second cell controller and to a backup interface of the first cell controller. In this arrangement the first cell controller also includes a control program for monitoring data communications with the additional rf port through its backup interface. The program is arranged to cause the first cell controller to assume primary communication functions of the additional rf port in the event primary

communications function of the second cell controller are inoperative for communication with the additional rf port.

5 In one arrangement the control program monitors boot requests from the rf port and detects communication failure by repeated boot requests. The primary and backup interfaces of the cell controllers may be defined by the software of the cell controllers, which designates certain of its interfaces as being primary to that cell controller and others as being backup interfaces. When a communication failure occurs the cell controller control program may be arranged to communicate with the other cell controller and to determine if primary communications functions of the
10 other cell controller have become operative. When the backup cell controller determines that the other cell controller has become operative and is capable of assuming primary communications with an rf port, the backup cell controller for the rf port can be arranged to send a reset signal to the rf port to cause it to send a boot request to it's primary cell controller.

15 In accordance with the invention there is provided a backup cell controller for use in a wireless local area network for data communications between a computer and at least one mobile unit. The backup cell controller includes at least one interface for connection to an rf port and a cell controller program for monitoring data communications from the rf port connected to the interface. The program is
20 arranged to cause the backup cell controller to assume primary communications functions with the rf port in the event primary communications functions of another cell controller are inoperative for communications with the rf port.

The backup cell controller preferably includes an additional interface by which the backup cell controller may provide primary communications functions
25 with an additional rf port connected to the additional interface. One way that the control program can monitor communications with an rf port is to monitor the boot requests and detect communications failure between an rf port and another cell controller by repeated boot requests from the rf port. The backup cell controller may be arranged to communicate with a primary cell controller following a determination
30 of inoperative primary communications with an rf port to determine if primary communications have subsequently become operative. The backup cell controller can

reset an rf port to cause it to reinitiate communications through it's primary cell controller.

In accordance with the invention there is provided a method for operating a wireless local area network for data communications between a computer and at least one mobile unit. There are provided first and second cell controllers connected to the computer, for example through a wired network. At least one rf port is connected to a primary interface of a first cell controller and connected to a backup interface of the second cell controller. The second cell controller monitors communications with the rf port by the backup interface and assumes primary communications with the rf port using the second cell controller in the event primary communications functions of the first controller are inoperative for communications with the rf port.

In a preferred arrangement there may be provided an additional rf port connected to a primary interface of the second cell controller and to a backup interface of the first cell controller. In this case the first cell controller monitors data communications with the additional rf port and causes the first cell controller to assume primary communications functions for the additional rf port in the event primary communications of the second cell controller are inoperative for communicating with the additional rf port. The monitoring may comprise monitoring boot requests from the additional rf port and detecting primary communications failure when the boot requests are repeated. Software may be used to define which interfaces of either cell controller comprise primary or backup interfaces. Following a determination of an inoperative primary communications there may be provided communications between the first and second cell controllers to determine if primary communications functions of the first cell controller have become operative. The rf port can be reset if the failed cell controller has been determined to be operative.

For a better understanding of the present invention, together with other and further objects, references made to the following description, taken in conjunction with the accompanying drawings, and its scope will be pointed out in the appended claims.

BRIEF DESCRIPTION OF THE DRAWING

Figures 1 is a block diagram illustrating an embodiment of a system using backup cell controllers in accordance with a preferred embodiment of the present invention.

5

DESCRIPTION OF A PREFERRED EMBODIMENT

Referring to Figure 1 there is shown a system 10 for providing a wireless local area network according to a preferred arrangement of the present invention. The system 10 is used with a wired network 12 having at least one computer 14. Those skilled in the art will recognize that additional computers and other equipment, such as a wide area network interface, an internet interface or a PBX may also be coupled to network 12.

In the embodiment illustrated in Figure 1, the wireless local area network 10 includes first and second cell controllers 18 labeled A and B and designated 18A and 18B. Cell controllers 18 are interfaced to network 12 by switching hub 16. As described in the referenced co-pending patent application, cell controllers 18A and 18B interface to network 12 and provide higher level medium access control (MAC) functions of an 802.11 wireless network, for example. The system 10 illustrated in Figure 1 includes two cell controllers, but those skilled in the art will recognize that any number of such cell controllers may be provided. The cell controllers 18A and 18B are arranged to be in backup mode to each other as will be further described. In the embodiment illustrated in Figure 1 cell controller 18A provides a hot standby backup for the rf ports serviced by cell controller 18B and cell controller 18B provides a hot standby backup for rf ports serviced by cell controller 18A.

Those skilled in the art will recognize that other arrangements of cell controllers are possible. For example, in a system having three cell controllers A, B and C, cell controller B may backup for cell controller A, cell controller C may backup for cell controller B and cell controller A may backup for cell controller C. Those skilled in the art will also recognize that it is possible to have a backup cell

controller that does not have its own rf ports associated with it and whose function is only to be in a hot standby backup condition for another cell controller. Cell controllers 18A and 18B are coupled by a common switching hub 20 to rf ports associated therewith. In the system 10 of Figure 1 rf ports 22A, 24A, 26A and 28A are associated with cell controller 18A as their primary cell controller. Likewise, rf ports 22B, 24B, 26B and 28B are associated with cell controller B as their primary cell controller. The wireless local area network 10 of Figure 1 may likewise include additional rf ports coupled to the cell controllers A, B and additional cell controllers. The illustrated embodiment shows four rf ports connected to each cell controller as a primary cell controller, but it will be recognized that there may be fewer or a larger number of rf ports allocated to each cell controller and the number of rf ports allocated to a cell controller may be different for each cell controller.

Rf ports 22, 24, 26, 28, A and B are arranged to form a wireless network for example within a facility, such as a hospital, industrial facility or university. Mobile units 30 may be arranged anywhere within the facility within range of an rf port and communicate with computer 14 over wireless network 10 and through wired network 12.

In accordance with a preferred arrangement of the present invention, rf ports 22A, 24A, 26A and 28A are connected to a primary interface of cell controller 18A. In this connection, the interface may be a software interface designating the particular interface with the rf port as being a primary rf port.

By designation of the interface with rf ports 22A, 24A, 26A and 28A, cell controller 18A primarily acts when it receives a boot request from any of these rf ports and thereafter boots or downloads a program to the rf port sending the boot request to initiate its operation. Likewise, rf ports 22B, 24B, 26B and 28B are primarily associated with cell controller B and have a primary interface therewith. Accordingly cell controller B initially responds to boot requests from its associated rf ports to download software to them.

All of the rf ports of the system 10 of Figure 1, in addition to being connected to a primary interface of their associated cell controllers, are also connected to a backup interface of the other cell controller. Thus, for example, rf port 22A is connected to a primary interface of cell controller 18A and to a backup interface of

cell controller 18B. Cell controllers 18A and 18B are provided with a control program to provide backup in the event of a failure of the other cell controller. For example, if cell controller 18A fails to operate, its corresponding rf port 22A will send a boot request message and not receive the requested initiation data. Rf port 22A, after a selected time period, such as one minute, will send a further boot request to cell controller 18A and continue to do so until cell controller 18A or another cell controller responds. Cell controller 18B monitors the boot requests from rf port 22A through the backup interface with rf port 22A. Cell controller 18B in a preferred arrangement keeps a count of the number of boot requests from an rf port. Thus, for example, if rf port 22A sends three or five boot request messages, then cell controller 18B may assume that cell controller 18A is inoperative, in that it cannot respond to the boot request from rf port 22A. In this case, cell controller 18B provides a backup for rf port 22A by downloading a boot program to rf port 22A that causes rf port 22A to become associated with cell controller 18B as a backup cell controller on a temporary basis. Cell controller 18B will likewise respond to boot requests from rf ports 24A, 26A and 28A in order to backup the failure of cell controller 18A. Likewise, cell controller 18A will backup the operation of cell controller 18B and monitor the boot request from rf ports 22B, 24B, 26B and 28B and provide a downloaded boot program to those cell controllers to initiate backup operation in the event a predetermined number of repetitive boot requests are received from any of those rf ports. Once a cell controller 18 has initiated backup operation for rf ports primarily associated with a different cell controller, the operation of the rf ports for communication with mobile units may proceed normally, subject to increased traffic which may slow down the operation of that particular cell controller. In a preferred arrangement once a cell controller has assumed operation as a backup cell controller for rf ports which are primarily associated with a different cell controller it will send inquiry messages to the cell controller primarily responsible for the rf ports to determine if that cell controller has resumed operation. Such inquiry messages may be sent, for example, every three to five minutes. When a cell controller providing backup service for rf ports primarily associated with a different cell controller determines that the other cell controller has become operational, as a result of receiving an appropriate response to an inquiry message, it can then send a reset

signal to the rf ports for which it is providing backup service. The reset signal causes the rf ports to reinitiate the boot process by sending a boot request to their primary cell controller, which, if operative, will download the appropriate software. In the event the primary cell controller is still not operational to provide the primary
5 software to the requesting rf ports, the backup cell controller monitors the boot request and may again assume backup operation for such rf ports.

Those skilled in the art will recognize that other modes of operation are possible than those specifically described above. For example a cell controller may determine malfunction in another cell controller by monitoring signals from the other
10 cell controller and thereby not monitor the boot request from the rf ports. In addition a cell controller may determine that a different cell controller has become operational when it receives valid communications from the other cell controller.

While there have been described what are believed to be the preferred embodiments of the present invention, those skilled in the art will recognize that other
15 and further changes and modifications may be made thereto without departing from the spirit of the invention, and it is intended to claim all such changes and modifications as fall within the true scope of the invention.

CLAIMS

1. A wireless local area network for data communications between a computer and at least one mobile unit, comprising:
 - first and second cell controllers connected to said computer;
 - 5 at least one rf port connected to a primary interface of said first cell controller and connected to a back-up interface of said second cell controller; and
 - a control program in said second cell controller monitoring data communications with said at least one rf port via said back-up interface, said program being arranged to cause said second cell controller to assume primary
 - 10 communications functions with said at least one rf port in the event primary communications functions of said first cell controller are inoperative for communication with said at least one rf port.
2. A network as specified in claim 1 wherein there is provided at least one additional rf port connected to a primary interface of said second cell
- 15 controller and to a back-up interface of said first cell controller, and wherein said first cell controller includes a control program for monitoring data communications with said additional rf port via said back-up interface of said first cell controller, said program being arranged to cause said first cell controller to assume primary communications functions of said additional rf port in the event primary
- 20 communications functions of said second cell controller are inoperative for communication with said additional rf port.
3. A network as specified in claim 1 wherein said control program monitors boot requests from said at least one rf port and detects communication failure by repeated boot requests.
- 25 4. A network as specified in claim 1 wherein said primary and back-up interfaces are defined by software of said cell controllers.
5. A network as specified in claim 1 wherein said second cell controller control program is arranged to communicate with said first cell controller

following a determination of inoperative primary communications to determine if primary communications functions of said first cell controller have become operative.

6. A network as specified in claim 5 wherein said second cell controller program is arranged to reset said at least one rf port when said first cell
5 controller's primary communications functions are determined to be operative.

7. A back-up cell controller for use in a wireless local area network for data communications between a computer and at least one mobile unit, comprising:

at least one interface for connection to an rf port; and
10 a cell controller program monitoring data communications from an rf port connected to said interface, said program being arranged to cause said back-up cell controller to assume primary communications functions with said rf port in the event primary communications functions of another cell controller are inoperative for communication with said rf port.

8. A back-up cell controller as specified in claim 7 wherein said
15 cell controller includes at least one additional interface, said additional interface and said control program being arranged to provide primary communications functions with an additional rf port connected to said additional interface.

9. A back-up cell controller as specified in claim 7 wherein said
20 control program monitors boot requests from said rf port connected to said interface and detects communication failure by repeated boot requests from said rf port.

10. A back-up cell controller as specified in claim 7 wherein said
cell controller control program is arranged to communicate with another cell controller following a determination of inoperative primary communications with said
25 rf port to determine if primary communications functions have become operative.

11. A back-up cell controller as specified in claim 10 wherein said cell controller program is arranged to reset said rf port if said primary communications are determined to be operative

12. A method for operating a wireless local area network for data communications between a computer and at least one mobile unit, comprising:
providing first and second cell controllers connected to said computer;
5 providing at least one rf port connected to a primary interface of said first cell controller and connected to a back-up interface of said second cell controller; and
monitoring data communications using said second cell controller with said at least one rf port via said back-up interface, and assuming
10 primary communications with said at least one rf port using said second cell controller in the event primary communications functions of said first cell controller are inoperative for communication with said at least one rf port.
13. A method as specified in claim 12 wherein there is provided at least one additional rf port connected to a primary interface of said second cell
15 controller and to a back-up interface of said first cell controller, further including monitoring data communications with said additional rf port via said back-up interface of said first cell controller, and causing said first cell controller to assume primary communications functions of said additional rf port in the event primary communications functions of said second cell controller are inoperative for
20 communication with said additional rf port.
14. A method as specified in claim 12 wherein said monitoring comprises monitoring boot requests from said at least one rf port and detecting communication failure by repeated boot requests.
15. A method as specified in claim 12 further including defining
25 said primary and back-up interfaces using software in said cell controllers.
16. A method as specified in claim 12 further including communicating between said first and second first cell controllers following a determination of inoperative primary communications, to determine if primary communications functions of said first cell controller have become operative.

17. A method as specified in claim 16 further including resetting said at least one rf port if said first cell controller primary communications are determined to be operative




FIG. 1

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US04/17199

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : G06F 11/00

US CL : 714/11

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 714/11, 10, 13, 4

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2001/0055283 A1 (BEACH) 27 December 2001 (27.12.2001), entire document	1-17
A	US 2002/0099972 A1 (WALSH et al) 25 July 2002 (25.07.2002), entire document	1-17
A	US 5,835,696 (HESS) 10 November 1998 (10.11.1998), entire document	1-17
A	US 6,760,859 B1 (KIM et al) 6 July 2004 (06.07.2004), entire document	1-17



Further documents are listed in the continuation of Box C.



See patent family annex.

Special categories of cited documents:	
* "A" document defining the general state of the art which is not considered to be of particular relevance	* "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
* "E" earlier application or patent published on or after the international filing date	* "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
* "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	* "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
* "O" document referring to an oral disclosure, use, exhibition or other means	* "&" document member of the same patent family
* "P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

05 September 2004 (05.09.2004)

Date of mailing of the international search report

15 SEP 2004

Name and mailing address of the ISA/US

Mail Stop PCT, Attn: ISA/US
 Commissioner for Patents
 P.O. Box 1450
 Alexandria, Virginia 22313-1450

Facsimile No. (703) 305-3230

Authorized officer

Robert Beausoliel

Telephone No. 703-305-3900

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.